


THE **PET & PAT-SERIES** TORQUE WRENCH POWER UNITS ARE PERFECTLY DESIGNED FOR OPERATING THE TW AND LPC -SERIES HYDRAULIC TORQUE WRENCHES.

They have a three stage pump for faster operation under load and incorporate a hydraulic oil cooler providing cool operation under continuous use. A 6 metre remote hand pendant is standard and one or two tools can be operated at one time due to the multi outlet pump block.



ROLL CAGE

for portability and protection

LIQUID FILLED PRESSURE GAUGE

has 1% accuracy and can be recalibrated. Scale is mpa/psi

ELECTRIC MOTOR

1.1 kW/240 Volt 50Hz induction motor 7.2 amp

OIL COOLER

electric fan operated for continuous duty operation

3 STAGE PUMP

for increased speed under load

MULTIPLE TOOL OUTLETS

for operating one or two tools simultaneously

ADJUSTABLE TORQUE CONTROL

for accurate torque settings

6M REMOTE PENDANT

through a 24 Volt transformer for safety. Incorporates motor ON/OFF button and ADV/AUTO RETRACT button

PET-1114

Model No.	Pressure Rating (bar)	Motor	Flow (Lpm)			Oil Capacity (L)	Dry Weight (kg)
			1st Stage 0-70 bar	2nd Stage 70-300 bar	3rd Stage 300-700 bar		
PET-1114	700	240 Volt / 50Hz	8	1.8	0.8	7.4	31
PAT-1114	700	1.1 kW Air	7	1.6	0.8	7.4	27

LIQUID FILLED PRESSURE GAUGE

has 1% accuracy and can be recalibrated. Scale is mpa/psi

AIR MOTOR

1.1 kW Ingersoll Rand®

ADJUSTABLE TORQUE CONTROL

for accurate torque settings

MULTIPLE TOOL OUTLETS

for operating one or two tools simultaneously

ROLL CAGE

for portability and protection

6M REMOTE PENDANT

incorporates motor ON/OFF button and ADV/AUTO RETRACT button

OIL COOLER

keeps oil cool during heavy duty operation

3 STAGE PUMP


for increased speed under load

AIR FILTER/LUBRICATOR

for efficient operation



PAT-1114



POWER REQUIREMENT

**Electric 240 Volt 50 Hz
Air 1,400 Lpm @ 6.2 bar**

FLOW

3 stage

MAXIMUM OPERATING PRESSURE

700 bar

Torque Wrench Hoses

Model No.	Length (m)	Description
TWH-04	4	Twin hose set to suit torque wrenches complete with male and female screw couplers at both ends. 700 bar working pressure. 2,800 bar min. burst.
TWH-06	6	
TWH-10	10	
TWH-15	15	



Did you know...

The **PET & PAT** hydraulic torque wrench power units are supplied with an oil cooler to allow continuous operation of hydraulic torque wrenches.



Torque Wrench Couplings

Model No.	Thread	Description	Suits Tool Model No.
CH-2	1/8"-NPT Male	Male half screw coupling complete with metal dust cap*	TW07, TW1, LPC2
CR-2	1/8"-NPT Male	Female half screw coupling complete with metal dust cap*	TW07, TW1, LPC2
CS-2	1/8"-NPT Male	Coupling set with metal dust caps* includes CH-2 and CR-2	TW07, TW1, LPC2
CH-4	1/4"-NPT Female	Male half screw coupling complete with metal dust cap*	TW3 THROUGH TW50 LPC4 THROUGH LPC30
CR-4	1/4"-NPT Male	Female half screw coupling complete with metal dust cap*	TW3 THROUGH TW50 LPC4 THROUGH LPC30
CS-4		Coupling set with metal dust caps* includes CH-4 and CR-4	TW3 THROUGH TW50 LPC4 THROUGH LPC30



Snap couplings available. Consult Durapac for further information.

* Dust cap/s not shown