



型式·SLF

公稱型號	花鍵軸承套尺寸								軸徑 d h7	滾珠列	基本額定負荷		基本額定扭矩		容許靜力矩		質量	
	D	L	A	B	F	油孔 Q	W	安裝孔 X x Y x Z			C	C ₀	C _T	C _{0T}	M _{A1}	M _{A2}	花鍵外筒 g	花鍵軸 kg/m
SLF 6	14	25	30	8	7.5	1	22	3.4x6.5x4.5	6	2	137	225	0.46	0.76	0.39	3.48	36.7	0.04
SLF 8	16	27	32	8	7.5	1.5	24	3.4x6.5x4.5	8	2	137	225	0.60	0.99	0.39	3.82	47	0.39
SLF 10	21	33	42	9	10.5	1.5	32	4.5x8x4	10	2	285	397	1.62	2.25	0.95	8.53	100	0.60
SLF 13	24	36	44	9	11	1.5	33	4.5x8x4.5	13	2	396	540	2.89	3.94	1.50	12.46	117	1.03
SLF 16	31	50	51	10	18	2	40	4.5x8x6	16	2	545	849	4.77	7.43	3.71	26.09	226	1.56
SLF 20	35	56	58	10	18	2	45	5.5x9.5x5.4	20	2	724	1109	7.90	12.09	5.53	38.00	303	2.44
SLF 25	42	71	65	13	26.5	3	52	5.5x9.5x8	25	4	1003	1593	21.99	43.01	10.35	68.59	454	3.80
SLF 30	47	80	75	13	30	3	60	6.6x11x8	30	4	1160	1980	30.26	62.93	15.68	93.27	646	5.50
SLF 40	64	100	100	18	36	4	82	9x14x12	40	4	2972	4033	105.37	176.05	36.59	246.34	1446	9.73
SLF 50	80	125	124	20	46.5	4	102	11x17.5x12	50	4	4086	5615	179.89	304.35	51.58	428.72	2785	15.24