



型式・SLT

公稱型號	花鍵軸承套尺寸			鍵槽尺寸		軸徑		滾珠列	基本額定負荷		基本額定扭矩		容許靜力矩		質量	
	D	L	L1	油孔 Q	b H8	t $+0.05$ 0	d h7		C	C <sub>0</sub>	C <sub>T</sub>	C <sub>0T</sub>	M <sub>A1</sub>	M <sub>A2</sub>	花鍵外筒 g	花鍵軸 kg/m
									kgf	kgf	kgf · m	kgf · m	kgf · m	kgf · m		
SLT 6	14	25	10.5	1	2.5	1.2	6	2	137	225	0.46	0.76	0.39	3.48	14	0.04
SLT 8	16	27	10.5	1.5	2.5	1.2	8	2	137	225	0.60	0.99	0.39	3.82	16	0.39
SLT 10	21	33	13	1.5	3	1.5	10	2	285	397	1.62	2.25	0.95	8.53	37	0.60
SLT 13	24	36	15	1.5	3	1.5	13	2	396	540	2.89	3.94	1.50	12.46	52	1.03
SLT 16	31	50	17.5	2	3.5	2	16	2	545	849	4.77	7.43	3.71	26.09	130	1.56
SLT 20	35	56	29	2	4	2.5	20	2	724	1109	7.90	12.09	5.53	38.00	176	2.44
SLT 25	42	71	36	3	4	2.5	25	4	1003	1593	21.99	43.01	10.35	68.59	281	3.80
SLT 30	47	80	42	3	4	2.5	30	4	1160	1960	30.26	62.93	15.68	93.27	407	5.50
SLT 40	64	100	52	4	6	3.5	40	4	2972	4033	105.37	176.05	36.59	264.34	858	9.73
SLT 50	80	125	58	4	8	4	50	4	4086	5615	179.89	304.35	51.58	428.72	1787	15.24